

1U 17" RACK MOUNT LCD MONITOR



- Mounted with smooth action ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable Lexan™ covering.
- Optional Composite and S-Video inputs.

GENERAL SPECIFICATIONS

Dimensions:

19.0" (W) x 1.75" (H) x 19.0" (D)

Weight:

27 lbs

Power (TFT Display):

90 - 260 VAC, 50/60 Hz.

60 Watts maximum

On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values

Plug & Play:

DDC1 and DDC2B

Temperature:

Operating: 0°C to 50°C

Storage: -20°C to 60°C

Humidity:

Operating: 10 to 85% RH (max)

Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

Input Connector:

Display: 15-pin mini D-Shell

Colors Available:

Black..

DISPLAY SPECIFICATIONS

Display Type:

Active matrix TFT LCD

Colors:

16.7 million colors

Contrast Ratio:

1000:1 typ.

Brightness:

250 cd/m² typ.

Viewing Angle:

Horizontal: 170°

Vertical: 160°

Response Time:

5ms.

Resolution:

640 x 350

640 x 480

800 x 600

1024 x 768

1280 x 1024

Display Area:

17" Diagonal

Horizontal Frequency:

31.5 to 80 KHz

Vertical Frequency:

56 to 75 Hz.

Specifications subject to change without notice.

MODEL NUMBER

RMM-607(X)(X)

