



17 and 19 inch Multi input LCD Console Drawers

Optimize rack space. Maximize rack monitoring
DVI-D-USB & VGA-USB, Audio, Hub




↑ (USB Port for device access)

Features

- 1U 17 or 19 inch LCD Console Drawer
- DVI & VGA Port
- Front 1xUSB, Rear 2xUSB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse)
- 104-key keyboard with touch pad mouse.
- USB 2.0 Keyboard & Mouse
- Self-locking and auto release rails for ultra convenience.
- Build in 2x 2 watts speakers

Options

- Composite Video input
- HDMI or Display Port input
- 3G / HD / SD –SDI Broadcast grade input
- 48V, 24V or 12V DC Power




Rear of KVM-1701PD-M2 / KVM-1901PD-M2

Part No.	KVM-1701PD-M2	KVM-1901PD-M2	
Direct no. of Computers	1		
KVM Connectors	DVI-D, VGA, USB		
LCD	Size	17"	19"
	Backlight	LED	LED
	Resolution	1280 x 1024	1280 x 1024
	Max.color	16.7M	16.7M
	Luminance	250cd/m2	250cd/m2
	View Angel (H/V)	176 / 170	170 / 176
Contrast Ratio	1000 : 1	1000 : 1	
USB HUB	1x Front , 2x Rear USB 2.0 Type A for peripheral USB devices		
Touch Screen	YES , for option (Driver needed)		
KB/Mouse Emulation	USB 2.0		
Audio	1 x 3.5 mm audio jack		
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)		
Power	100-240V AC 50/60Hz via IEC Type power cord		
Environment	Operation temp: 0 to 50°C		
	Storage temp: -20 to 60°C		
	Humidity: 10% - 90%, non-condensing		
	Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP		
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) / 14.5KG	448x42x580mm (WxHxD) / 14.5KG	
Packing Dimensions / Gross weights	710x160x780mm (WxHxD) / 19KG	710x160x780mm (WxHxD) / 19KG	

Accessories

1.8 meter IEC Type Power Cord , 1.8 meter DVI-D Cable, 1.8 meter VGA Cable , 1.8 meter USB Cable , 1.8 meter Audio Cable (each one)



Rear of KVM-1701/1901PD-M2

