


Rear of KVM-MSC-108E



Rear of KVM-MSC-116E

Optional Remote CAT6 Receiver

- Connecting by CAT6 cable, Remote console up to 300 meters,
- Pure hardware solution make network independent,
- No software required
- Dual user access at remote site.



Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance support or failure recovery via secure SSL authentication and encryption



Features

- Multi-users simultaneous access, up to four consoles.
- Capable of connecting 16 or 8 servers in 1U.
- Support combo interface VGA-USB & VGA-PS/2.
- USB local console, CAT6 console extension port up to 300 meters, two optional remote IP console.
- Cascade up to 8 levels, support mixed CAT6 & DB15 Combo KVM switch.
- Mixed PS2/USB/SUN & MAC with multi-platform switch Capability.
- Auto scan for monitoring PCs, easy select via push button, Hot keys and OSD.
- Hot pluggable, no software or driver required.
- Easy and quick installation.

Part No.	MSC-108E	MSC-116E	
No. of Computers	8	16	
Max. no. of Computers	232 (Daisy Chain)	240 (Daisy Chain)	
KVM port connector	HD DB15 Female		
Optional Remote CAT6 Console	1x RJ45 connector up to 300 meters with CAT6 cable Remote receiver : 1x HD DB15 for VGA (up to 1024x768 resolution) 2x USB Type A for KB / Mouse 1x HD DB15 KVM port for connecting an extra PC		
Optional IP Remote Console	1x RJ45 connector for 10/100M Ethernet (up to 1600x1200 resolution) 1x DB9 male connector for modem, Null modem and serial power control 1x mini USB 2.0 receptacle		
Daisy Chain	2x Centronics 36 pin (Female), up to 8 levels		
Hot keys	Scroll-Lock, Caps-Lock, Num-Lock, Alt-Ctrl-Win		
Compatibility	Mix PCs, SUNs and MACs, support Win7/Vista/2003/XP, Linux, Unix		
Power	100-240V AC 50/60Hz external power adapter		
Environment	Operation temp.: 0 to 50°C Storage temp : -20 to 60°C Humidity : 10% - 90%, non-condensing		
Physical Dimensions / Net Weights	448mm (W) x 167mm (D) x 44mm (H) / 3kg		
Packing Dimensions / Gross Weights	560*120*250mm / 3.5kg		
Relate Items			
CVU-018	1.8meter 2-in-1 KVM Cable - USB & VGA	CVP-018	1.8meter 2-in-1 KVM Cable – PS/2 & VGA
CVU-030	3.0meter 2-in-1 KVM Cable - USB & VGA	CVP-030	3.0meter 2-in-1 KVM Cable – PS/2 & VGA
CVU-050	5.0meter 2-in-1 KVM Cable - USB & VGA	CVP-050	5.0meter 2-in-1 KVM Cable – PS/2 & VGA
DCC-300R	CAT6 console receiver up to 300 Meters		
DIP-101	KVM over IP Module for Remote Bios Level Access		