


Rear of KSC-108EP



Rear of KSC-116EP

## Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



## Features

- Capable of connecting 16 or 8 servers in 1U.
- Support USB interface VGA-USB.
- USB local console, optional remote IP console.
- 2x USB 2.0 ports sharing USB peripheral for computers.
- Mixed PS2/USB/SUN& MAC with multi-platform switch Capability.
- Auto scan for monitoring PCs, easy select via push button, Hot keys and OSD.
- Hot pluggable, no software or driver required.
- Easy and quick installation.

| Part No.                           | KSC-108EP   | KSC-116EP |
|------------------------------------|---|-----------|
| No. of Computers                   | 8   | 16        |
| KVM port connector                 | HD DB15 Female  |           |
| Local Console                      | 1x HD DB15 for VGA ( up to 1920x1440 resolution )<br>2x USB Type A for KB / Mouse   |           |
| Optional IP Remote Console         | 1x RJ45 connector for 10/100M Ethernet ( up to 1600x1200 resolution )<br>1x DB9 male connector for modem, Null modem and serial power control<br>1x mini USB 2.0 receptacle |           |
| USB HUB                            | 2x USB 2.0 Type A for USB peripheral devices  |           |
| Hot keys                           | Scroll-Lock, Caps-Lock, Num-Lock, Alt-Ctrl-Win  |           |
| Compatibility                      | Mix PCs, SUNs and MACs, support Win7/Vista/2003/XP, Linux, Unix   |           |
| Power                              | 100-240V AC 50/60Hz external power adapter  |           |
| Environment                        | Operation temp.: 0 to 50°C<br>Storage temp : -20 to 60°C<br>Humidity : 10% - 90%, non-condensing  |           |
| Physical Dimensions / Net Weights  | 448mm (W) x 167mm (D) x 44mm (H) / 3kg  |           |
| Packing Dimensions / Gross Weights | 560*120*250mm / 3.5kg   |           |

### Relate Items

|         |   |         |  |
|---------|---|---------|--|
| CVU-018 | 1.8meter 2-in-1 KVM Cable - USB & VGA           | CVP-018 | 1.8meter 2-in-1 KVM Cable – PS/2 & VGA |
| CVU-030 | 3.0meter 2-in-1 KVM Cable - USB & VGA           | CVP-030 | 3.0meter 2-in-1 KVM Cable – PS/2 & VGA |
| CVU-050 | 5.0meter 2-in-1 KVM Cable - USB & VGA           | CVP-050 | 5.0meter 2-in-1 KVM Cable – PS/2 & VGA |
| DIP-101 | KVM over IP Module for Remote Bios Level Access |         |  |