



Rear of MCC-116E



Rear of MCC-132E

Optional Remote CAT6 Receiver

- Connecting by CAT6 cable, Remote console up to 300 meters,
- Pure hardware solution make network independent,
- No software required
- Dual user access at remote site.



Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance support or failure recovery via secure SSL authentication and encryption



Features

- Multi-users simultaneous access, up to four consoles.
- Capable of connecting 32 or 16 servers in 1U.
- Support combo interface VGA-USB & VGA-PS/2.
- Up to 40 meters between servers to KVM switch.
- USB local console, CAT6 console extension port up to 300 meters, Two optional remote IP console.
- Cascade up to 8 levels, support mixed CAT6 & DB15 Combo KVM switch.
- Mixed PS2/USB/SUN & MAC with multi-platform switch Capability.
- Auto scan for monitoring PCs, easy select via push button, Hot keys and OSD.
- Hot pluggable, no software or driver required.
- Easy and quick installation.

Part No.	MCC-116E	MCC-132E
No. of Computers	16	32
Max. no. of Computers	240 (Daisy Chain)	256 (Daisy Chain)
KVM port connector	RJ 45	
Local Console	1x HD DB15 for VGA (up to 1920x1440 resolution) 2x USB Type A for KB / Mouse	
Optional Remote CAT6 Console	1x RJ45 connector up to 300 meters with CAT6 cable Remote receiver : 1x HD DB15 for VGA (up to 1024x768 resolution) 2x USB Type A for KB / Mouse 1x HD DB15 KVM port for connecting an extra PC	
Optional IP Remote Console	1x RJ45 connector for 10/100M Ethernet (up to 1600x1200 resolution) 1x DB9 male connector for modem, Null modem and serial power control 1x mini USB 2.0 receptacle	
Daisy Chain	2x Centronics 36 pin (Female) , up to 8 levels	
Hot keys	Scroll-Lock , Caps-Lock , Num-Lock , Alt-Ctrl-Win	
Compatibility	Mix PCs ,SUNs and MACs , support Win7/Vista/2003/XP , Linux , Unix	
Power	100-240V AC 50/60Hz external power adapter	
Environment	Operation temp.: 0 to 50°C Storage temp : -20 to 60°C Humidity : 10% - 90% , non-condensing	
Physical Dimensions / Net Weights	448mm (W) x 167mm (D) x 44mm (H) / 3kg	
Packing Dimensions / Gross Weights	560*120*250mm / 3.5kg	

Relate Items

DGU	CAT6 KVM Dongle - USB & VGA	DGP	CAT6 KVM Dongle - PS/2 & VGA
DGD	CAT6 KVM Dongle-USB&DVI	DCC-300R	CAT6 console receiver up to 300 Meters
DIP-101	KVM over IP Module for Remote Bios Level Access		