



DSRD 19



Rugged 2U rackmount drawer with dual 19" LCD monitors. The displays fold together, rotate, and slide in for storage.



Technical Specifications

PRODUCT	DSRD 19
DISPLAY	DUAL 19" SXGA 1280 X 1024
VIEWING ANGLE	DISPLAYS TILT ~15° FROM VERTICAL
PORTS	INTERNAL USB 2.0 HUB + 2X USB 2.0 INPUTS ON FRONT + 1X USB 2.0 INPUTS ON REAR, ANALOG VGA, DVI-D, DISPLAYPORT FOR EACH DISPLAY
POWER SUPPLY	115/230 VAC, 50/60HZ, 100W MAX
KEYBOARD & MOUSE	101 KEYS BACKLIT KEYBOARD WITH TOUCHPAD AND ADJUSTABLE BRIGHTNESS. RESISTIVE TOUCHPAD
DIMENSIONS	HEIGHT: 2U (3.46") WIDTH: 17.76" DEPTH: 25.89"
WEIGHT	~45 LBS
TEMPERATURE	MIL-STD-810E (501.4, 502.4), OPERATING: 0 ~ 50°C, NON-OPERATING: -40 ~ 70°C
HUMIDITY	MIL-STD-810E (507.2), RELATIVE HUMIDITY: 5% TO 95% OPERATING, NON-CONDENSING
ALTITUDE	MIL-STD-810E (500.3), OPERATING: 15,000 FT (4571.8 M), NON-OPERATING: 40,000 FT (12,192 M)
VIBRATION	MIL-STD-810E (514.4), OPERATING: 10 TO 500 HZ 1.04 G (RMS)
SHOCK	MIL-STD-810E (516.4), OPERATING: 15 G, 8 MS 1/2 SINE, NON-OPERATING: 40 G, 8 MS 1/2 SINE
DROP	4" STAND ALONE, 39" TRANSIT DROP IN TRANSIT CASE
REGULATION	CE, FCC, CCC
WARRANTY	1 YEAR PARTS AND LABOR

*

